

TECHNICAL DATA SHEET

D - 900 - 50 DOOR FINISHING INSTRUCTIONS

MMI DOORS ARE PRIME PAINTED (TO ANSI STANDARDS) AT THE FACTORY WITH AN ALKYD EMULSION TYPE PRIMER. THIS FINISH IS DESIGNED TO PROVIDE PROTECTION DURING NORMAL STORAGE, SHIPPING AND INSTALLATION AND TO PROVIDE A UNIFORM BASE FOR FINISH PAINTING. IT IS RECOMMENDED THAT OIL WATER BASE PAINT BE APPLIED AFTER.

DO'S AND DON'TS

- DO:**
- 1.- LIGHTLY SAND ENTIRE SURFACE WITH 320 - 400 GRIT SANDPAPER , WIPE CLAEEN
 - 2.- RE-PRIME ANY BARE METAL AREA WITH PRIMER SUITEBLE FOR OVER BARE STEEL.
 - 3.- FILL ANY DENTS OR DEEP SCRATCHES WITH STANDARD AUTO BOBY FILLER;
(FOLLOWING INSTRUCTIONS LABELED ON AUTO BODY FILLER)

- DON'T :**
- 1.- TOP COAT WITH A WATER BASE PAINT IF BARE METAL IS SHOWING.
 - 2.- USE ANY LACQUERS
 - 3.- USE ANY POLYURETHANES OR EPOXYS.
EXCEPTIONS : SOME EPOXYS AND POLYURETHANES WORK WELL BUT MUST DE TESTED FIRST.

REMEMBER: MATERIAL IS SHIPPED AS PRIMED PAINTED ONLY AND SOME SCRATCHES ARE NORMAL; PLEASE FOLLOW RECOMMENDATIONS ABOVE FOR EXTENDED LIFE OF PRODUCT.

MMI PRODUCTS (WHERE APPLICABLE) ARE MANUFACTURED TO ANSI STANDARDS

Issue Date: January 2006

REVISED : 02/01/2009

