

MMI DOORS ARE PRIME PAINTED (TO ANSI STANDARDS) AT THE FACTORY WITH AN ALKYD EMULSION TYPE PRIMER. THIS FINISH IS DESIGNED TO PROVIDE PROTECTION DURING NORMAL STORAGE, SHIPPING AND INSTALLATION AND TO PROVIDE A UNIFORM BASE FOR FINISH PAINTING. IT IS RECOMMENDED AN OIL BASE PAINT TO BE APPLIED AS A FINISH COAT.

DO'S AND DONT'S

- DO:**
1. LIGHTLY SAND THE ENTIRE SURFACE WITH 230 - 400 GRIT SANDPAPER, WIPE CLEAN
 2. FILL ANY DENTS OR DEEP SCRATCHES WITH STANDARD AUTO BODY FILLER; (FOLLOW AUTO BODY FILLER INSTRUCTIONS)
 3. RE-PRIME ANY BARE METAL AREA WITH PRIMER SUITABLE FOR BARE STEEL.
- DON'T:**
1. TOP COAT WITH A WATER BASE PAINT
 2. USE ANY LACQUERS
 3. USE ANY POLYURETHANES OR EPOXIES. EXCEPTIONS: SOME EPOXIES AND POLYURETHANES WORK WELL BUT MUST BE TESTED FIRST

REMEMBER

MATERIAL IS SHIPPED AS PRIME PAINTED ONLY AND SOME SCRATCHES ARE NORMAL; PLEASE FOLLOW RECOMMENDATIONS ABOVE FOR EXTENDED LIFE OF PRODUCT.

MMI PRODUCTS (WHERE APPLICABLE) ARE MANUFACTURED TO ANSI STANDARDS.